

Deckshield Wall Guard (NR/SBR Rubber)



Description

Deckshield Wall Guard is a rubber guard designed to provide excellent wall protection from vehicles when manoeuvring in car park structures.

Uses

Primarily for use in multi-storey car parks, but can also be applied in loading bays, warehouses and other industrial units.

Benefits

- Provides excellent protection
- Reduces damage to walls
- Weather & UV resistant
- Suitable for indoor and outdoor use
- Good water resistance
- Good impact strength

Colours

Available in black with or without the yellow insert.

Technical Information

Specific Gravity	1.45±0.05
Hardness ASTM D2240	Shore A. 75±5
Tensile Strength ASTM D412	12.0 N/mm ²
Elongation at Break ASTM D412	325%, min.
Compression Set ASTM D395	35% (max) at 70°C for 22 hours
Tear Resistance – Die C ASTM D624	30KN/m, min.
Water Resistance	Good
Weather Resistance	Good

Ageing Test (ASTM D573)

Below are the results for the ageing resistance after the duration of the time and temperature

(Ageing Resistance 70hrs @ 100°C)

Change in Hardness (Points)	+5
Change in Tensile Strength	-25%
Change in Elongation at Break	-22%

Sizes

Available in the following sizes
 20mm (thickness) x 200 mm (width)
 25mm (thickness) x 200 mm (width)
 50mm (thickness) x 200 mm (width)

Available in 2000mm, 4000mm & 6000mm lengths.

Material

Natural Rubber / SBR (for exposed decks use EPDM)

Further Information

To ensure you are specifying a fit for purpose flooring for your project please consult our Technical Advisors on the number below or visit our website to register your interest in specifying one of the most durable floors on the market.