

Deckshield Corner Guard (EPDM)



Description

Deckshield Corner Guard is a rubber guard designed to provide excellent wall protection from vehicles when manoeuvring round corners.

Uses

Primarily for use in multi-storey car parks, but can also be applied in loading bays, warehouses and other industrial units.

Benefits

- Provides excellent protection
- Reduces damage to walls
- Weather & UV resistant
- Suitable for indoor and outdoor use
- Good water resistance
- Good impact strength

Colours

Available in black with or without the yellow insert.

Technical Information

Specific Gravity	1.10 to 1.30
Hardness ASTM D2240	Shore A. 75±5
Tensile Strength ASTM D412	10.0 N/mm ²
Elongation at Break ASTM D412	200%, min.
Compression Set ASTM D395	30% (max) at 70°C for 22 hours
Tear Resistance – Die C ASTM D624	30KN/m, min.
Water Resistance	Good
Weather Resistance	Good

Ageing Test (ASTM D573)

Below are the results for the ageing resistance after the duration of the time and temperature

(Ageing Resistance 70hrs @ 100°C)

Change in Hardness (Points)	+10
Change in Tensile Strength	-35%
Change in Elongation at Break	-40%

Sizes

Available in the following sizes
75mm x 75mm x 1000mm (length)
100mm x 100mm x 1000mm (length)
120mm x 120mm x 1200mm (length)

Material

EPDM used for exposed decks (also available in SBR).

Further Information

To ensure you are specifying a fit for purpose flooring for your project please consult our Technical Advisors on the number below or visit our website to register your interest in specifying one of the most durable floors on the market.