

Deckshield Speed Guard (EPDM)



Description

Deckshield Speed Guard is a rubber speed hump designed to ensure safe speeds for vehicles manoeuvring through car park structures.

Uses

Primarily for use in multi-storey car parks, but can also be applied in loading bays, warehouses and other industrial units.

Benefits

- Abrasion resistant
- Encourages safety around car park environments
- Weather & UV resistant
- Suitable for indoor and outdoor use
- Good water resistance

Colours

Available in black or black & yellow.

Technical Information

Specific Gravity	1.10 to 1.30
Hardness ASTM D2240	Shore A. 75±5
Tensile Strength ASTM D412	10.0 N/mm ²
Elongation at Break ASTM D412	200%, min.
Compression Set ASTM D395	30% (max) at 70°C for 22 hours
Tear Resistance – Die C ASTM D624	30KN/m, min.
Water Resistance	Good
Weather Resistance	Good

Ageing Test (ASTM D573)

Below are the results for the ageing resistance after the duration of the time and temperature

(Ageing Resistance 70hrs @ 100°C)

Change in Hardness (Points)	+10
Change in Tensile Strength	-35%
Change in Elongation at Break	-40%

Sizes

Available in the following sizes
 300mm x 60mm
 350mm x 50mm
 400mm x 50mm
 400mm x 65mm
 400mm x 68mm
 460mm x 75mm

Material

EPDM used for exposed decks (also available in SBR).

Further Information

To ensure you are specifying a fit for purpose flooring for your project please consult our Technical Advisors on the number below or visit our website to register your interest in specifying one of the most durable floors on the market.