

Flowcoat SF150



Description

Flowcoat SF150 is a solvent-free two component high build epoxy coating system, primary designed to provide a degree of chemical and abrasion resistance to all concrete surfaces.

Uses

Flowcoat SF150 may be used as hard-wearing pigmented floor coating in areas such as plant rooms, warehouses, store rooms, light production and process areas.

Benefits

- High Performance Coating
- Chemical Resistance
- Excellent Abrasion Resistance
- Solvent Free
- Seamless & Hygienic Finish
- Slip resistant finish can be tailored to suit to client requirement.

Project References

Available on request.

Standard Colour Chart



Ivory



Yellow



Dark Red



Light Blue



Blue



Dark Green




Light Grey



Mid Grey




Dark Grey



Black

System Design



Model Specification

Product: Flowcoat SF150

Finish: Gloss

Thickness: 0.25mm-0.75mm

Colour: _____

Preparatory work and application in accordance with suppliers instructions.

Manufacturer: Flowcrete Middle East FZCO

Telephone : Customer Service +971 4 886 4728

Substrate Requirements

Concrete or screed substrate should be a minimum of 25N/mm², free from laitance, dust and other contamination. The substrate should be dry up to 75% RH as per BS8204 and free from rising damp and ground water pressure.

Products Included in this System

Flowcoat SF150

For actual coverage rates, refer to the appropriate specification.

For slip resistant dressings, please consult our Technical Advisors.

Detailed application instructions are available upon request.

Installation Service

The installation should be carried out by a Flowcrete approved applicator with a documented quality assurance scheme. Obtain details of our approved contractors by contacting our customer service team or enquiring via our website at www.flowcrete.ae

Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs, maintenance and cleaning. Environmental and health considerations are controlled during the manufacture and application of the products by Flowcrete staff and fully trained and experienced contractors.

Focus on the Floorzone

Flowcrete Middle East FZCO is a division of the Flowcrete Group, world leaders in specialist industrial and commercial flooring. Systems available include: underfloor heating systems, floor screeds, surface damp proof membranes, decorative floor finishes, seamless terrazzo, car park deck waterproofing and corrosion protection systems... to name just a few. Our corporate objective is to satisfy your flooring needs.

Technical Information

The figures that follow are typical properties achieved in laboratory tests at 20°C and at 50% Relative Humidity.

Fire Resistance	BS476:Part:7:Surface spread of flame: Class 1
Slip Resistance	TRRL Pendulum Slip Test Dry: 80 Wet: depends on specification
Thermal Resistance	Tolerant up to 70°C
Water Permeability	Nil – Karsten test (impermeable)
Surface Hardness	180secs. Koenig Hardness Test
Chemical Resistance	Contact Technical Department
Abrasion Resistance	Taber Abrader: 5 mg loss per 1000 cycles (1 kg load using CS17 wheels) BS8204-2 Grade AR2
Compressive Strength	>70 N/mm ² (BS6319)
Flexural Strength	>42 N/mm ² (BS6319)
Tensile Strength	>22 N/mm ² (BS6319)
Bond Strength	Greater than cohesive strength of 25 N/mm ² concrete. >1.5 MPa.

Speed of Cure

	10°C	20°C	30°C
Light Traffic	48 hrs	16 hrs	12 hrs
Full traffic	72 hrs	48 hrs	40 hrs
Full chemical cure	12 days	7 days	7 days

Aftercare - Cleaning and Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

Important Note

Flowcrete's products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which can be obtained on request.

Further Information

To ensure you are specifying a fit for purpose flooring for your project please consult our Technical Advisors on the number below or visit our website to register your interest in specifying one of the most durable floors on the market.